


Contact adhesive Energoflex® Extra

Description

	Energoflex® Extra contact adhesive is used for joining insulation junctions.		Article
	Volume	Approximate consumption of 1L of contact adhesive:	
	Pipes 6 mm thick	240-300 linear m	
	Pipes 9 mm thick	160-200 linear m	
	Pipes 13 mm thick	110-140 linear m	
	Pipes 20 mm thick	70-90 linear m	
	Pipes 25 mm thick	50-60 linear m	
	Rolls and plates	~5 m ²	
Package:	0,5 L metal can	EFXADH0/5EXT	
	0,9 L metal can	EFXADH0/8EXT	
	2,6 L metal can	EFXADH2/6EXT	
Storage temperature:	От + 10 до + 40°C		
Use temperature:	From + 10 to + 40°C		

Packaging



Cans of 0,5 L are packed into cartons with dimensions of 560 x 230 x 190 mm.

Cans of 0,8 L are packed into cartons with dimensions of 560 x 230 x 280 mm.

Cans of 0,5 L are packed into cartons with dimensions of 450 x 250 x 230 mm.

designation		package type	quantity per package, pcs.	gross weight, kg	package volume, m ³
Contact adhesive Energoflex® Extra	0,5 L	Carton	20	10,50	0,024
	0,8 L		20	16,50	0,036
	2,6 L		6	15,50	0,026