

Contact adhesive Energoflex® Extra

Description



Energoflex® Extra contact adhesive is used for joining insulation junctions.

Article

Volume

Approximate consumption of 1L of contact adhesive:

Pipes 6 mm thick	240-300 linear m
Pipes 9 mm thick	160-200 linear m
Pipes 13 mm thick	110-140 linear m
Pipes 20 mm thick	70-90 linear m
Pipes 25 mm thick	50-60 linear m
Rolls and plates	~5 m ²

Package:

0,5 L metal can	EFXADH0/5EXT
0,9 L metal can	EFXADH0/8EXT
2,6 L metal can	EFXADH2/6EXT

Storage temperature: От + 10 до + 40°C

Use temperature:

From + 10 to + 40°C

Packaging



Cans of 0,5 L are packed into cartons with dimensions of 560 x 230 x 190 mm.

Cans of 0,8 L are packed into cartons with dimensions of 560 x 230 x 280 mm.

Cans of 0,5 L are packed into cartons with dimensions of 450 x 250 x 230 mm.

designation		package type	quantity per package, pcs.	gross weight, kg	package volume, m ³
Contact adhesive Energoflex® Extra	0,5 L	Carton	20	10,50	0,024
	0,8 L		20	16,50	0,036
	2,6 L		6	15,50	0,026