


Contact adhesive Energoflex® Extra

Description

| | | | |
|---|--|---|---------|
|  | Energoflex® Extra contact adhesive is used for joining insulation junctions. | | Article |
| | Volume | Approximate consumption of 1L of contact adhesive: | |
| | Pipes 6 mm thick | 240-300 linear m | |
| | Pipes 9 mm thick | 160-200 linear m | |
| | Pipes 13 mm thick | 110-140 linear m | |
| | Pipes 20 mm thick | 70-90 linear m | |
| | Pipes 25 mm thick | 50-60 linear m | |
| | Rolls and plates | ~5 m ² | |
| Package: | 0,5 L metal can | EFXADH0/5EXT | |
| | 0,9 L metal can | EFXADH0/8EXT | |
| | 2,6 L metal can | EFXADH2/6EXT | |
| Storage temperature: | От + 10 до + 40°C | | |
| Use temperature: | From + 10 to + 40°C | | |

Packaging



Cans of 0,5 L are packed into cartons with dimensions of 560 x 230 x 190 mm.
Cans of 0,8 L are packed into cartons with dimensions of 560 x 230 x 280 mm.
Cans of 0,5 L are packed into cartons with dimensions of 450 x 250 x 230 mm.

| designation | | package type | quantity per package, pcs. | gross weight, kg | package volume, m ³ |
|------------------------------------|-------|--------------|----------------------------|------------------|--------------------------------|
| Contact adhesive Energoflex® Extra | 0,5 L | Carton | 20 | 10,60 | 0,024 |
| | 0,8 L | | 20 | 16,50 | 0,036 |
| | 2,6 L | | 6 | 15,50 | 0,026 |