


## Contact adhesive Energoflex® Extra

### Description

	Energoflex® Extra contact adhesive is used for joining insulation junctions.		Article
	<b>Volume</b>	<b>Approximate consumption of 1L of contact adhesive:</b>	
	Pipes 6 mm thick	240-300 linear m	
	Pipes 9 mm thick	160-200 linear m	
	Pipes 13 mm thick	110-140 linear m	
	Pipes 20 mm thick	70-90 linear m	
	Pipes 25 mm thick	50-60 linear m	
	Rolls and plates	~5 m <sup>2</sup>	
<b>Package:</b>	0,5 L metal can	EFXADH0/5EXT	
	0,9 L metal can	EFXADH0/8EXT	
	2,6 L metal can	EFXADH2/6EXT	
<b>Storage temperature:</b>	От + 10 до + 40°C		
<b>Use temperature:</b>	From + 10 to + 40°C		

### Packaging



**Cans of 0,5 L are packed into cartons with dimensions of 560 x 230 x 190 mm.**  
**Cans of 0,8 L are packed into cartons with dimensions of 560 x 230 x 280 mm.**  
**Cans of 0,5 L are packed into cartons with dimensions of 450 x 250 x 230 mm.**

designation		package type	quantity per package, pcs.	gross weight, kg	package volume, m <sup>3</sup>
Contact adhesive Energoflex® Extra	0,5 L	Carton	20	10,50	0,024
	0,8 L		20	16,50	0,036
	2,6 L		6	15,50	0,026