




Reinforced tape Energoflex®

Description

	Reinforced self-adhesive tape Energoflex® of gray color is applied at installation of Energoflex® Super insulation. Due to the reinforcing net the tape possesses high rupture strength.		Article
	Approximate expenditure:	1,15 - 1,45 of the straight piping length of a pipeline; 26 m on 10 m ² isolated surface	
	Width:	48 mm	
	Height:	10 m	EFXL04810ARSKGR
		25 m	EFXL04825ARSKGR
50 m		EFXL04850ARSKGR	
Temperature:	Not below 10°C		

	Reinforced self-adhesive tape Energoflex® of black color is applied at installation of Energoflex® Black Star insulation. Due to the reinforcing net the tape possesses high rupture strength.		Article
	Approximate expenditure:	1,15 - 1,45 of the straight piping length of a pipeline; 26 m on 10 m ² isolated surface	
	Width:	48 mm	
	Height:	25 m	EFXL04825ARSKBK
		50 m	EFXL04850ARSKBK
Temperature:	Not below 10°C		

	Reinforced self-adhesive tape Energoflex® of blue and red colors is applied at installation of Energoflex® Super Protect insulation. Due to the reinforcing net the tape possesses high rupture strength.		Article
	Approximate expenditure:	1,15 - 1,45 of the straight piping length of a pipeline;	
	Width:	48 mm	
	Height, colour:	25 m, blue	EFXL04825ARSKBL
		25 m, red	EFXL04825ARSKRD
Temperature:	Not below 10°C		

Packaging



Tape in length of 50 m is packed in cartons with dimensions of 410 x 300 x 275 mm.

Tape in length of 25 m is packed in cartons with dimensions of 445 x 225 x 150 mm.

Tape in length of 10 m is packed in cartons with dimensions of 558 x 190 x 150 mm.

designation		package type	quantity per package, pcs.	gross weight, kg	package volume, m ³
Reinforced tape Energoflex®	48 mm x 50 m grey	Carton	36	14,76	0,034
	48 mm x 50 m black		36	14,76	0,034
	48 mm x 25 m grey		24	6,24	0,015
	48 mm x 25 m black		24	6,24	0,015
	48 mm x 25 m blue		24	6,24	0,015
	48 mm x 25 m red		24	6,24	0,015
	48 mm x 10 m grey		36	4,00	0,016