



Maximum service temperature	R₂₅
+ 70°C	0,75 m ² /KW

Indicator	Value
Printing step	5 cm
Water absorption by volume per 24 hours, no more, than	3%

- STRONG EXTERNAL COVERING
- HIGH THERMAL RESISTANCE
- DECREASE IN SHOCK NOISE
- RELIABLE FIXING OF TACKER BRACKETS
- THE MARKING FOR LAYING OF PIPES



Plates and mats from the expanded polystyrene, covered with a polymeric fabric with a marking

Item	Article	Thickness, mm	Width, m	Length, m	Quantity per package, m ²	Price including VAT, RUR/m ²
Insulating mate Energofloor® Tacker 30/1,0-3,2 DES-sg	EFRM3013/2TKR	30	1,0	3,2	3,2	427,20
Insulating plate Energofloor® Tacker 30/1,0-1,6 DES-sg	EFRP3011/6TKR	30	1,0	1,6	8	427,20

Packed into white-orange polyethylene packets. Package dimensions:

Insulation mate Energofloor® Tacker – packed into white-orange polyethylene packets, diameter 400 mm, height 1000 m, package volume 0,13 m³

Insulation plate Energofloor® Tacker – 1000 x 800 x 300 mm, package volume 0,24 m³

Accessories

Item	Article	Unit of measurement	Price including VAT, RUR
Damper tape Energofloor® 10/0,1-11	EFRL1010011DM	roll	448,06
Damper tape Energofloor® 10/0,15-11	EFRL1015011DM	roll	806,52
Tape-hermetic Energofloor® 50mm x 50m	EFRL05050DM	roll	292,82
Montage knife	EFXKNIFE	piece	2490,05

Price list dd. February 20, 2017