



Indicator	Value	
	thickness 20 mm	thickness 30 mm
Thermal resistance R <sub>25</sub>	0,5 m <sup>2</sup> •K/W	0,75 m <sup>2</sup> •K/W
Maximum service temperature	+ 70°C	
Water absorption by volume at full immersion within 24 h, no more, than	3,0 %	
Printing step	5 mm	

- STRONG EXTERNAL ALUMINIZED POLIMERIC COVERING
- HIGH THERMAL RESISTANCE
- DECREASE IN SHOCK NOISE
- RELIABLE FIXING OF TACKER BRACKETS
- THE MARKING FOR LAYING OF PIPES



Plates and mats from the expanded polystyrene, covered with an aluminized polymeric fabric with a marking

Item	Article	Thickness, mm	Width, m	Length, m	Quantity per package, m <sup>2</sup>	Price without VAT, RUB/m <sup>2</sup>
Insulating mate Energofloor® Tacker AL 20/1,0-4,8 DES-sg	EFRM2014/8TKRAL	20	1,0	4,8	4,8	647,43
Insulating plate Energofloor® Tacker AL 20/1,0-1,6 DES-sg	EFRP2011/6TKRAL	20	1,0	1,6	14,4	647,43
Insulating mate Energofloor® Tacker AL 30/1,0-3,2 DES-sg	EFRM3013/2TKRAL	30	1,0	3,2	3,2	863,51
Insulating plate Energofloor® Tacker AL 30/1,0-1,6 DES-sg	EFRP3011/6TKRAL	30	1,0	1,6	9,6	863,51

Mates Energofloor® Tacker AL packed into cartons with dimensions of 1020 x 395 x 395 mm, package volume 0,160 m<sup>3</sup>.

Plates Energofloor® Tacker AL packed into cartons with dimensions of 1010 x 815 x 370 mm, package volume 0,305 m<sup>3</sup>.

#### Accessories

Item	Article	Unit of measurement	Price without VAT, RUB
Damper tape Energofloor® 10/0,1-11	EFRL1010011DM	roll	591,86
Damper tape Energofloor® 10/0,15-11	EFRL1015011DM	roll	1065,38
Montage knife Energoopro®	EPRKNIFE	piece	3760,35

Price list dd. March 4, 2024