



Maximum service temperature + 95°C	μ-factor ≥9 000	λ ₂₀ ≤0,040 W/(m·°C)
---------------------------------------	--------------------	------------------------------------



- RESISTANCE TO UV-RADIATION
- RESISTANCE TO MECHANICAL DAMAGES
- RESISTANCE TO THE CONCRETE, CEMENT, GYPSUM, LIME
- SERVICE LIFE IN THE OPEN AIR, NOT LESS THAN 16 YEARS



Tubes from polyethylene foam in a protecting covering being 2 m in length

Insulation is mounted on a copper pipe	
Inches	Outer diameter, mm
1/4	6,35
3/8	9,53
1/2	12,70
5/8	15,88

Inner diameter of insulation, mm	Insulation thickness			
	6 mm			
	Standard size	Article	Quantity per package, m	Price without VAT, RUB/m
6	6/6-2	EFX T006062BSSPL	480	22,74
10	10/6-2	EFX T010062BSSPL	320	25,64
12	12/6-2	EFX T012062BSSPL	280	30,45
15	15/6-2	EFX T015062BSSPL	200	33,50

Packed into cartons with dimensions of 2050 x 395 x 295 mm, package volume 0,240 m³.

Accessories

Item	Article	Unit of measurement	Price without VAT, RUB
Adhesive Energopro® 0,8 L	EPRADH0/8B	can	1199,66
Adhesive Energopro® 2,0 L	EPRADH2/0B	can	2641,76
Adhesive diluent Energopro® 1,0 L	EPRDIL1/0B	can	988,91
Reinforced self-adhesive tape Energopro® 48mm x 50m, grey	EPRL04850ARSKGR	roll	746,76
Reinforced self-adhesive tape Energopro® 48mm x 50m, grey, C	EPRL04850ARSKGRC	roll	746,76
Reinforced self-adhesive tape Energopro® 48mm x 25m, grey	EPRL04825ARSKGR	rol	387,66
Reinforced self-adhesive tape Energopro® 48mm x 25m, grey, C	EPRL04825ARSKGRC	roll	387,66

Price list dd. June 19, 2024