



Maximum service temperature	μ -factor	λ_{20}
+ 95°C	$\geq 9\,000$	$\leq 0,040$ W/(m·°C)



- RESISTANCE TO UV-RADIATION
- RESISTANCE TO MECHANICAL DAMAGES
- RESISTANCE TO THE CONCRETE, CEMENT, GYPSUM, LIME
- SERVICE LIFE IN THE OPEN AIR, NOT LESS THAN 16 YEARS



Tubes from polyethylene foam in a protecting covering being 2 m in length

Insulation is mounted on a copper pipe	
Inches	Outer diameter, mm
1/4	6,35
3/8	9,53
1/2	12,70
5/8	15,88

Inner diameter of insulation, mm	Insulation thickness			
	6 mm			
	Standard size	Article	Quantity per package, m	Price without VAT, RUB/m
6	6/6-2	EFXT006062BSSPL	480	25,47
10	10/6-2	EFXT010062BSSPL	320	28,71
12	12/6-2	EFXT012062BSSPL	280	34,10
15	15/6-2	EFXT015062BSSPL	200	37,52

Packed into cartons with dimensions of 2050 x 395 x 295 mm, package volume 0,240 m³.

Accessories

Item	Article	Unit of measurement	Price without VAT, RUB
Adhesive Energopro® 0,8 L	EPRADH0/8B	can	1319,63
Adhesive Energopro® 2,0 L	EPRADH2/0B	can	2905,94
Adhesive diluent Energopro® 1,0 L	EPRDIL1/0B	can	1087,81
Reinforced self-adhesive tape Energopro® 48mm x 50m, grey	EPRL04850ARSKGR	roll	821,43
Reinforced self-adhesive tape Energopro® 48mm x 50m, grey, C	EPRL04850ARSKGRC	roll	821,43
Reinforced self-adhesive tape Energopro® 48mm x 25m, grey	EPRL04825ARSKGR	rol	426,42
Reinforced self-adhesive tape Energopro® 48mm x 25m, grey, C	EPRL04825ARSKGRC	roll	426,42

Price list dd. February 17, 2025

