



Reinforced tape Energopro®

Description

	Reinforced self-adhesive tape Energopro® of gray color is applied at installation of Energoflex® Super insulation. Due to the reinforcing net the tape possesses high rupture strength.		Article
	Approximate expenditure:	1,15 - 1,45 of the straight piping length of a pipeline; 26 m on 10 m ² isolated surface	
	Width:	48 mm	
	Height:	25 m	EPRL04825ARSKGRR EPRL04825ARSKGR
		50 m	EPRL04850ARSKGRR EPRL04850ARSKGR
Temperature:	Not below 10°C		

	Reinforced self-adhesive tape Energopro® of black color is applied at installation of Energomax®, Energoflex® Black Star and Energoflex® Super Protect Black insulation. Due to the reinforcing net the tape possesses high rupture strength.		Article
	Approximate expenditure:	1,15 - 1,45 of the straight piping length of a pipeline; 26 m on 10 m ² isolated surface	
	Width:	48 mm	
	Height:	25 m	EPRL04825ARSKBKR EPRL04825ARSKBK
		50 m	EPRL04850ARSKBKR EPRL04850ARSKBK
Temperature:	Not below 10°C		

	Reinforced self-adhesive tape Energopro® of blue and red colors is applied at installation of Energoflex® Super Protect insulation. Due to the reinforcing net the tape possesses high rupture strength.		Article
	Approximate expenditure:	1,15 - 1,45 of the straight piping length of a pipeline;	
	Width:	48 mm	
	Height, colour:	25 m, blue	EPRL04825ARSKBLR EPRL04825ARSKBL
		25 m, red	EPRL04825ARSKRDR EPRL04825ARSKRD
Temperature:	Not below 10°C		

Packaging



Tapes in length of 50 m are packed in cartons with dimensions of 298 x 283 x 283 mm.
Tapes in length of 25 m are packed in cartons with dimensions of 303 x 335 x 236 mm.

designation		package type	quantity per package, pcs.	gross weight, kg	package volume, m ³
Reinforced tape Energopro®	48 mm x 50 m grey	Carton	24	10,09	0,024
	48 mm x 50 m black		24	10,09	0,024
	48 mm x 25 m grey		36	8,09	0,024
	48 mm x 25 m black		36	8,09	0,024
	48 mm x 25 m blue		36	8,09	0,024
	48 mm x 25 m red		36	8,09	0,024