



Indicator	Value	
	thickness 20 mm	thickness 30 mm
Thermal resistance R ₂₅	0,5 m ² ·K/W	0,75 m ² ·K/W
Maximum service temperature	+ 70°C	
Water absorption by volume at full immersion within 24 h, no more, than	3,0 %	
Printing step	5 mm	

- STRONG EXTERNAL ALUMINIZED POLIMERIC COVERING
- HIGH THERMAL RESISTANCE
- DECREASE IN SHOCK NOISE
- RELIABLE FIXING OF TACKER BRACKETS
- THE MARKING FOR LAYING OF PIPES



Plates and mats from the expanded polystyrene, covered with an aluminized polymeric fabric with a marking

Item	Article	Thickness, mm	Width, m	Length, m	Quantity per package, m ²	Price without VAT, RUB/m ²
Insulating mate Energofloor® Tacker AL 20/1,0-4,8 DES-sg	EFRM2014/8TKR	20	1,0	4,8	4,8	404,59
Insulating plate Energofloor® Tacker AL 20/1,0-1,6 DES-sg	EFRP2011/6TKR	20	1,0	1,6	14,4	404,59
Insulating mate Energofloor® Tacker AL 30/1,0-3,2 DES-sg	EFRM3013/2TKR	30	1,0	3,2	3,2	469,23
Insulating plate Energofloor® Tacker AL 30/1,0-1,6 DES-sg	EFRP3011/6TKR	30	1,0	1,6	9,6	469,23

Mates Energofloor® Tacker AL packed into cartons with dimensions of 1020 x 395 x 395 mm, package volume 0,160 m³.

Plates Energofloor® Tacker AL packed into cartons with dimensions of 1010 x 815 x 370 mm, package volume 0,305 m³.

Accessories

Item	Article	Unit of measurement	Price without VAT, RUB
Damper tape Energofloor® 10/0,1-11	EFRL1010011DM	roll	478,91
Damper tape Energofloor® 10/0,15-11	EFRL1015011DM	roll	862,06
Tape-hermetic Energofloor® 50mm x 50m	EFRL05050DM	roll	360,92
Montage knife Energopro®	EPRKNIFE	piece	2304,35

Price list dd. June 23, 2021